


1. INFORMATION FOR THE INSTALLER

1.1. RECEIPT OF MATERIAL

- + Check the condition of the package:
 - + In the event of any visible damage, write this down on the delivery note.
 - + In the event of any hidden damage, inform of such within 72 hours.
- + No claims will be admitted for transport reasons if any of these instructions are not followed.

1.2. HANDLING & STORAGE

- + We recommend you keep the NATURFLOOR-W panels in their original packaging until they are ready to be installed. In the event that any panel needs repackaging, this shall be done in the same conditions as the original packaging.
- + These same instructions are also valid for cut parts.
- + Improper storage / handling of the panels can cause permanent deformation in the panels.
- + During transport, the NATURFLOOR-W panels must be properly strapped, bearing in mind that the straps move up and down easily and can quickly become frayed. They must always be transported horizontally.
- + The panels must be stored in a closed, ventilated area, at a room temperature of 10°C to 27°C and with an air humidity level between 30 and 70%.
- + The panels must not be stored vertically; they must always be stored horizontally with a distance between supports that does not exceed 800mm.
- + The floor on which the pallet rests must be free of any materials or substances that may cause damage.
- + We recommend you avoid exposing the two sides of the NATURFLOOR-W panels to different humidity and temperature conditions.



1.3. CONDITIONING BEFORE AND DURING INSTALLATION

- + 72h before its installation, store the material in the center of the room in which it is going to be placed, removing the protective plastic that surrounds the panels, so that they can acclimatize correctly to the conditions of the interior room in which they are going to be installed.
- + Once the packaging has been opened, we recommend you only take out the NATURFLOOR-W panels that are going to be used immediately. The rest must remain in storage in the same conditions as they were in the original packaging.
- + Do not support or store the packages in contact with the walls, leaving them at least 0,5m apart. In addition, it is necessary to leave a separation between the boxes, so as to guarantee a ventilation flow, so that the slats are subjected to the same humidity and temperature conditions on both sides.
- + Stack the packages flat, supported by four equidistant battens or other elements that allow maintaining a distance from the ground and in which the packages are supported uniformly (pallets, etc.).
- + The floor that supports the pallet must be free of materials that could cause damage.
- + The conditions in the room before and during the installation must be of a temperature between 15°C – 27°C and a relative humidity between 30 – 70%.

1.4. MACHINING AND DRILLING

- + Due to their composition, the NATURFLOOR-W boards are relatively hard. The tools used for its cutting must be more resistant than for most woods or wood-based materials. The use of polycrystalline diamond (PCD) tools is recommended due to their long life.
- + The cutting tool must be perfectly sharpened or it could cause splintering on the sides. For further details about machining, please see the NATURFLOOR-W catalogues or contact PARKLEX PRODEMA (parklexprodema@parklexprodema.com).

1.5. REPACKAGING

- + Does not apply.

1.6. INSTALLATION INSTRUCTIONS

- + NATURFLOOR-W is a product designed for use as interior floor covering that can be installed floating or glued.
- + The temperature and humidity conditions of both the enclosure (slab, walls and ceilings) and the material are critical before and during the installation process. All installations must follow the technical instructions described in the NATURFLOOR-W Technical Guide.
- + PARKLEX PRODEMA will not be responsible for the use of any other assembly system that is not included in the NATURFLOOR-W Technical Guide, unless expressly authorized by the PARKLEX PRODEMA Technical Department.
- + The use of safety googles and gloves during the panels' handling and cutting processes is strongly recommended. Likewise, all the habitual health & safety requirements must be taken into account, as regards dust extraction and collection, fire prevention and protection measures, etc.

1.7. CLEANING

- + Dirt does not stick easily to the surface of the NATURFLOOR-W boards. However, if the surface becomes dirty it can be cleaned with lukewarm water mixed with liquid detergent, using a soft cloth and never rubbing the surface dry.
- + For persistent stains, conventional commercial bleaches can be used, always diluted in the concentrations recommended by the manufacturer.
- + Never use detergents containing abrasive particles.
- + Cloths, sponges or paper with abrasive agents, for example Scotch Brite or sandpaper, should never be used as they can damage the surface.
- + Do not use excess water, or leave puddles of water on the floor.
- + Cleaning with pressurized water machines is not allowed.
- + It is always recommended to carry out a cleaning test on a small area of the material, in order to verify the effectiveness of the procedure, and only then proceed with the entire surface.
- + The use of solvents and chemical cleaning products must always be carried out respecting the corresponding safety and hygiene rules.
- + There is a list of commercial products that can be used. For more details, consult the PARKLEX PRODEMA Technical Department.

1.8. PACKAGING WASTE

- + The packaging is made up of three different materials: cardboard, wood and plastic, which can be easily separated and recycled.

2. INFORMATION FOR USERS

2.1. ENVIRONMENTAL CONDITIONS DURING USE

- + The conditions in the room during the life of the product must be at a temperature between 15°C – 27°C and a relative humidity between 40 – 65%.
- + To achieve these conditions, humidification / dehumidification systems may be necessary.
- + If the indicated conditions are not met, deformations, cracks and in some cases even permanent damage may occur to the installed material.

2.2 MAINTENANCE

- + The NATURFLOOR-W boards do not require any maintenance. In the case of dirt, please see the 2.3. CLEANING section.
- + Protect from direct sunlight.
- + When moving heavy furniture, it should be lifted and not pushed.
- + In case of using casters for chairs and furniture, only soft type casters should be used.
- + Always use special wheels for wooden floors.
- + You must protect the legs of chairs and tables with a self-adhesive felt protector.
- + In uses in which the surface of the floor directly limits with the outside, a clean transit area (mat type) of adequate dimensions must be incorporated.

2.3. CLEANING

- + Refer to section 1.7. CLEANING.

2.4. REPAIR

- + Natural wood is a delicate material. There is no established method for repairing NATURFLOOR-W boards. Damaged panels must be replaced with new panels. If you need to uninstall a damaged slat, contact the PARKLEX PRODEMA Technical Department.

2.5. INFORMATION FOR UNINSTALLATION

- + NATURHARDPANEL-W panels | NATURPANEL-W are part of an interior paneling, whose main components are easily separable and recyclable.
- + Recycling: the slats can be recycled. Recycling possibilities include its use as a filler material in wood-based panels for use in construction.
- + Deposit in landfill: the specifications that regulate the production and management of construction and demolition waste will be followed, as well as the applicable local regulations. It is also possible to recover it in incinerators for industrial use.

2.6. BOARD END OF LIFE

- + Reuse: The reuse of the NATURFLOOR-W panels will be encouraged in other applications with different requirements.
- + Recycling: the cellulose fibers in the core and the thermoset wood veneer can be recycled. The recycling possibilities include use as filling material in wood-based panels for the construction industry.
- + Landfill or dumping: All specifications controlling the production and management of construction and demolition waste will be followed, as well as any local regulations that may apply. It might also be utilized in industrial incinerators.

- + Sub-structure: the wooden, aluminum or steel profiles can be directly reused for their original application or recycled if the buildings are carefully deconstructed.

FOR FURTHER INFORMATION, PLEASE SEE THE PARKLEX PRODEMA CATALOGUE OR CONTACT PARKLEX PRODEMA (parklexprodema@parklexprodema.com).