


1	NATURCLAD
2	Screws
2.1	Panel fastener metal
2.2	Channel fastener - by others
2.3	Wall fixing screw- by others
3	Profiles
3.1	Aluminum J profile
3.2	Aluminum HAT profile
3.3	Clamp
3.4	Jamb profile - by others
3.5	Sill profile - by others
3.6	Coronation profile - by others
4	Water resistant barrier - by others
5	Thermal insulation - by others
6	Steel backing plate - by others
7	Vent. screen - by others

A	Required min. air chamber $\geq 3/4"$ (20mm)
B	Circulation of air $\geq 3/4"$ (20mm)
C	Horizontal expansion joint $1/16"$ (1mm)
D	Expansion joint $1/4" - 3/8"$ (6-10mm)
E	Panel thickness $5/16"$ (8mm)
F	Distance from the screws to panel edges $3/4" - 1 1/2"$ (20-40mm)



Measurements in inches are approximated. Real measurements in mm.

Scale 1:2

Measures: inch

PARKLEX PRODEMA
www.parklexprodema.com

PRODUCT	NATURCLAD	SYSTEM	LAP SIDING SYSTEM (METALLIC FRAME) WITH BACKING PLATE	DRAWN BY	Joseba Salbide	DATE	01/2022
PLAN#	NC1-04-A-J	TITLE	DETAIL J-J' // DOOR HEAD	APPROVED BY	Maialen Irastorza	PAGE	11 / 12