

# Environmental Product Declaration

In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:

HPL board with natural wood finish

**NATURSOFFIT - W**

From

Programme:	The International EPD <sup>®</sup> System, <a href="http://www.environdec.com">www.environdec.com</a>
Programme operator:	EPD International AB
EPD registration number:	S-P-05245
Publication date:	2022-01-18
Valid until:	2027-01-16

*An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com)*

Parklex Prodema Int. S.L.U.

**PARKLEX PRODEMA**



## General information

### Programme information

<b>Programme:</b>	The International EPD® System
<b>Address:</b>	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
<b>Website:</b>	<a href="http://www.environdec.com">www.environdec.com</a>
<b>E-mail:</b>	<a href="mailto:info@environdec.com">info@environdec.com</a>

ISO standard ISO 21930 and CEN standard EN 15804 serves as the core Product Category Rules (PCR)

Product category rules (PCR):

PCR 2019:14 Construction products, version 1.11

PCR review was conducted by:

The Technical Committee of the International EPD® System. See [www.environdec.com/TC](http://www.environdec.com/TC) for a list of members. Review chair: Claudia

A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat [www.environdec.com/contact](http://www.environdec.com/contact).

Independent third-party verification of the declaration and data, according to ISO 14025:2006:

External     Internal

Covering

EPD process certification     EPD verification

Third party verifier:

Tecnalia R&I Certificacion, SL

Auditor: Eva Larzabal

[info@tecnaliacertificacion.com](mailto:info@tecnaliacertificacion.com)

Accredited by: ENAC nº125/C-PR283 accreditation.

Procedure for follow-up of data during EPD validity involves third party verifier:

Yes     No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.

## Company information

Owner of the EPD: Parklex Prodema Int. S.L.U.

Description of the organisation:

Parklex Prodema Int. is a company dedicated to the manufacture of HPL boards with natural wood finish for NATURSOFFIT - W.

For Parklex Prodema Int. the design, innovation and quality are vital, but even more important is our respect and admiration for nature. The source of our materials and our inspiration. This is why we encourage sustainable construction, maximizing wellbeing and environmental efficiency in buildings.

### ASPEN ART MUSEUM

---

The museum itself is a work of art, created by prestigious architect Shigeru Ban, Winner of the Pritzker 2014, the same year that this Project was concluded.



This is how we became the first company in the world in our industry to obtain the ISO 14006 in ECOdesign. At Prodema, we also have the PEFC certification seal, which guarantees that our products were prepared with raw forest materials that were socially and environmentally managed in a responsible way.

Environmental Management System Certificate	UNE-EN ISO 14001 GA-2002/070
Ecodesign Management Systems Certification	UNE-EN ISO 14006 ED-0009/2010
Forest product custody chain Management Systems Certificate	PEFC/14-35-00025-AEN

Name and location of production site:

Maderas Mejoradas Industrial,s.a.  
Polígono Alkaiaga. C/ Baldrún 1  
31780 Bera - Navarra - Spain

Contact:

Fernando Encío  
Quality & Enviroment System Manager  
Email: [fernando.encio@parklexprodema.com](mailto:fernando.encio@parklexprodema.com)  
More information: <https://www.parklexprodema.com>

## Product information

Product name: HPL boards with natural wood finish. NATURSOFFIT - W

Product description:

NATURSOFFIT - W panels are made up of a high-density bakelite core, covered with a natural wood veneer treated with synthetic resin.

The Prodema NATURSOFFIT - W range is maintenance free and easy-to-install, making for an innovative solution to an age-old problem. The new range allows built at indoors or exterior surfaces. They're suitable for sheltered and horizontal downward applications such as underside balconies or canopies.

NATURSOFFIT - W panels are produced in two different ranges in relation to their fire behaviour, standard (S) and retardant to fire (F) for the improved fire reaction class.

Intended use of the construction product: As external finishes in ceilings



Technical data

TESTS	RESULTS	PROPERTY OR ATTRIBUTE	MEASURE UNIT	STANDARD
	FTSOFFIT Rev: 0			
<b>1. INSPECTION REQUIREMENTS</b>				
Colour, pattern and surface finish	Due to the fact that wood is a natural product, each veneer may be considered as unique. Colour and structure differences are considered as normal. Singularities such as knots and resin inclusions are not considered as defects, but as a part of the décor. There are differences in light fastness performances depending on the wood species and the source of the wood.			EN 438-8 Apto. 5.2.2.3
<b>2. DIMENSIONAL TOLERANCES</b>				
Thickness (t)	± 0,50	$8 \leq t \leq 10$	mm	EN 438-2 Apto. 5
Flatness (f)	5,0	t = 8 and 10	mm/m	EN 438-2 Apto. 9
Length and width	+10 / - 0	-	mm	EN 438-2 Apto. 8
Edge straightness	1,5	-	mm/m	EN 438-2 Apto. 7
Edge squareness	1,5	-	mm/m	EN 438-2 Apto. 8
<b>3. PHYSICAL PROPERTIES</b>				
Dimensional stability at elevated temperature	0,3	Longrain	% max	EN 438-2 Apto.17
	0,8	Crossgrain		
Resistance to impact by large diameter ball	≥ 1.800	Maximal height for which no visible surface cracking or imprint greater than 10 mm	mm	EN 438-2 Apto.21
Determination of graffiti resistance	Level 3	Permanent blue marker	Cleanability level	ASTM D 6578:2000
	Level 4	Spray red paint		
	Level 2	Wax black crayon		
	Level 1	Water based ink black marker		
<b>4. WEATHER RESISTANCE REQUIREMENTS</b>				
Resistance to artificial wheathering FOR MODERATE OUTDOOR CONDITIONS (EGS)	≥ 3	Contrast	Grey scale rating	EN 438-2 Apto.29 Rating according to EN 20105 – A02
	≥ 4	Aspect	Rating	
<b>5. CE SAFETY REQUIREMENTS</b>				
Reaction to fire	C-s2,d0	Euroclass	Classification	EN 13.501-1
Thermal resistance/Conductivity	0,266	Thermal conductivity (l)	W/m K	EN 12664
Water vapour permeability	110	Wet cup method	μ	EN 438-7 Apto 4.4
	250	Dry cup method		
Resistance to fixings	> 3.000	Screw holding value for t = 8 mm	N	EN 438-7 Apto 4.5
	> 4.000	Secrew holding value for t = 10 mm		
Flexural strength	≥ 80	Longrain	MPa	EN ISO 178
	≥ 80	Crossgrain		
Flexural Modulus	≥ 9.000	Longrain	MPa	EN ISO 178
	≥ 9.000	Crossgrain		
Resistance to climatic shock	≥ 4	Appearance	Rating	EN 438-2 Apto.19
	≥ 0,80	Flexural strength	Index Ds	
	≥ 0,80	Elastic modulus	Index Dm	
Density	≥ 1,35	Density	g/cm <sup>3</sup>	EN ISO 1.183
Resistance to wet conditions	≤ 5	Moisture absorbed	%	EN 438-2 Apto.15
	≥ 4	Appearance	rating	

## Product dimension features

- ✓ Length and width: 2440 mm x 1220 mm
- ✓ Thickness: 8, 10 mm
- ✓ Weight by surface area unit:

Kg/m <sup>2</sup>	Standard (S)	Standard (S)	Retardant to fire (F)	Retardant to fire (F)
	8mm	10mm	8mm	10mm
NATURSOFFIT - W	11,3	14,3	11,3	14,5

UN CPC code: 314 Boards and panel

## LCA information



Declared unit: The declared unit is the baseline reference for which all information is collected. In this study, the declared business unit “1m<sup>2</sup> of board” of the following typologies:

NATURSOFFIT - W	
Standard (S)	8mm
Standard (S)	10mm
Retardant to fire (F)	8mm
Retardant to fire (F)	10mm

Reference service life: Not relevant for this EPD.


Geographical scope: The geographical scope of this EPD is international.

Time representativeness: The data collection from factory (primary data) is from 2020/01/01 to 2020/12/31. The electricity mix is from 2020 year. In this study, no datasets older than 10 years were used.

Database(s) and LCA software used: All the data used to model the process and obtain the Life Cycle Inventory are specific data and they are representative of the different processes implemented during the manufacturing process. The data has been measured directly at the company's own premises. In addition, the most complete and highest quality European life cycle inventory database, Ecoinvent 3.6, has been used, as this database contains the most extensive and updated information and its scope coincides with the geographical, technological and temporal area of the project. The LCA was modelled with Simapro 9.1.1.1.

Description of system boundaries: According to the standard UNE-EN 15804\_2012+A2\_2020 (MARCH 2020) and PCR 2019:14 CONSTRUCTION PRODUCTS (version 1.11) the system boundary is cradle to gate with modules C1–C4 and module D (A1–A3 + C + D). The life cycle stages A4–A5, B1–B7 were excluded from the LCA study.

System diagram:



*System boundaries*

Manufacturing process:

The manufacturing process takes place over 5 steps:

1. Raw material reception and selection. In some cases, shearing is necessary to achieve appropriate dimensions.

2. Preparing packages, joining different layers of film and paper to be pressed later on.
3. Pressing.
4. Machining the boards, adjusting them to client requirements with an automatic saw.
5. Packaging the end product with the different protective layers required. Products are stored until dispatch.

#### Author of the Life Cycle Assessment:

IK ingenieria  
Av. Cervantes 51, Edif. 10, planta 5, dpto.  
48970 Basauri, Bizkaia (Spain)

#### Data quality

The environmental impact of the boards has been calculated. It is based on the international standards established for the development of environmental product declarations, such as ISO 14025 for the preparation of the environmental product declaration, ISO 14040 and ISO 14044 for the preparation of the life cycle analysis, UNE-EN 15804:2012+A2:2020 (MARCH 2020) and the Product Category Rules PCR - "2019:14 Construction products " (Version 1.11) of the CPC 314.

Data for raw material supply, transport to fabrication plant and production (A1-A3) is based on specific consumption data for the factory at Legorreta. Generic background datasets were used for the downstream processes. SimaPro v9.1.1.1. software was used to prepare the life cycle analysis together with the Ecoinvent 3.6 database. Characterization factors from EN15804: 2012 + A2:2019.

The geographical coverage is international. Technological coverage is typical or average.

#### Assumptions

The modularity principle, as well as the polluter-payer principle have been followed. The following assumptions have been made in this EPD:

- ✓ It does not include the manufacturing processes of the capital goods or spare parts and/or maintenance with a life of more than three years.
- ✓ The environmental impact of infrastructure for general management, office, and headquarters operations is not included.
- ✓ The impact caused by people (common activities, travel for work...) will not be considered.
- ✓ The processes associated with fuel production are intrinsically included in the indicators in ECOINVENT's database used in carrying out the LCA.
- ✓ The environmental impact of external transport has been calculated using lorries from the ECOINVENT 3.6 database, EURO 6. These lorries have been selected to reflect the most realistic scenario possible.

#### Cut-off rules

The standard ISO 14025 and the PCR -"2019:14 CONSTRUCTION PRODUCTS" indicate that the life cycle inventory data should include a minimum of 95% of the total inputs (materials and energy) for each stage. This cut-off rule does not apply for hazardous materials and substances. No such cut-off criteria have been taken into account in this study.

#### Allocation

Where necessary, such as auxiliary materials, water, waste generation, emissions and energy consumption, an allocation based in mass has been used.

Greenhouse gas emission from the use of electricity in the manufacturing phase

The mix of renewable energy used to produce certain raw materials and the in-factory production process is based in the year 2020. Specific renewable electricity mix with Guarantee of Origin, high voltage (direct emissions and losses in grid) electricity is considered for the manufacturing process.

Electricity mix	Amount	Units
Specific electricity mix with GoO	0,04	Kg CO2-eqv/kWh

## LCA Scenarios and additional technical information

Dismantling/demolition (module C1):

Since they are not products with a structural use, the energy consumption of this phase is considered not relevant.

Transport (module C2):

With a collection rate of 100%, the transports are carried out by lorry (EURO 6) over 50 km.

Waste processing (modules C3 and C4):

A recycling ratio of 43,53 %, energy recovery ratio of 41,79 %, incineration ratio of 13,78 % and a landfilled ratio of 0,9% is considered in accordance with the publication of the H2020 project "Absorbing the Potential of Wood Waste in EU Regions and Industrial Bio-based Ecosystems — BioReg" document "D1.1 EUROPEAN WOOD WASTE STATISTICS REPORT FOR RECIPIENT AND MODEL REGIONS" for Europe

(<https://ec.europa.eu/research/participants/documents/downloadPublic?documentIds=080166e5bf1792ce&appId=PPGMS>). These percentages are representative of the areas where the product is marketed.

In module C3 the boards waste treatment (chipping) is considered. In module C4 the impact of incineration process and the landfilling.

Recyclability potentials (module D):

Module D contains credits from the recycling and energy recovery of the boards in module C3. For the recycling process is considered that the board is collected and recycled for use in substitution of virgin wood chips. For energy recovery, use in substitution electricity and natural gas to produce heat.



Modules declared, geographical scope, share of specific data (in GWP-GHG indicator) and data variation:

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage	
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
Modules declared	X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X	
Geography	EU	EU	EU	ND	ND	ND	ND	ND	ND	ND	ND	ND	GLO	GLO	GLO	GLO	GLO	
Specific data used	>90%					-	-	-	-	-	-	-	-	-	-	-	-	-
Variation – products	No applicable					-	-	-	-	-	-	-	-	-	-	-	-	-
Variation – sites	No applicable					-	-	-	-	-	-	-	-	-	-	-	-	-

## Content information

Product components	NATURSOFFIT – W S 8mm			NATURSOFFIT – W S 10mm			NATURSOFFIT – W F 8mm			NATURSOFFIT – W F 10mm		
	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%
Plastics	1,20E-01	0,00%	0,00%	1,20E-01	0,00%	0,00%	1,20E-01	0,00%	0,00%	1,20E-01	0,00%	0,00%
Synthetic resins	3,99E+00	0,00%	0,00%	5,19E+00	0,00%	0,00%	4,41E+00	0,00%	0,00%	5,65E+00	0,00%	0,00%
Wood veneer	6,76E-01	0,00%	100,00%	6,76E-01	0,00%	100,00%	6,76E-01	0,00%	100,00%	6,76E-01	0,00%	100,00%
Paper	6,49E+00	25,00%	100,00%	8,34E+00	25,00%	100,00%	6,13E+00	25,00%	100,00%	8,00E+00	25,00%	100,00%
<b>TOTAL</b>	<b>1,13E+01</b>	<b>14,39%</b>	<b>63,57%</b>	<b>1,43E+01</b>	<b>14,56%</b>	<b>62,95%</b>	<b>1,13E+01</b>	<b>13,52%</b>	<b>60,04%</b>	<b>1,45E+01</b>	<b>13,85%</b>	<b>60,06%</b>

Packaging materials	Weight, kg	Weight-% (versus the product)	Weight, kg	Weight-% (versus the product)	Weight, kg	Weight-% (versus the product)	Weight, kg	Weight-% (versus the product)
Cardboard	2,04E-01	1,81%	2,58E-01	1,80%	2,04E-01	1,80%	2,58E-01	1,79%
Plastic	2,57E-01	2,27%	3,23E-01	2,25%	2,57E-01	2,26%	3,26E-01	2,25%
Wood	2,20E-01	1,95%	2,20E-01	1,54%	2,20E-01	1,94%	2,20E-01	1,53%
Steel	1,02E-02	0,09%	1,29E-02	0,09%	1,02E-02	0,09%	1,29E-02	0,09%
<b>TOTAL</b>	<b>6,91E-01</b>	<b>6,13%</b>	<b>8,15E-01</b>	<b>5,69%</b>	<b>6,91E-01</b>	<b>6,09%</b>	<b>8,17E-01</b>	<b>5,66%</b>

Packaging: Product packaging includes different layers of plastic films, pallets, chipboards, wooden wedges and steel strips.

No substances included in the Candidate List of Substances of Very High Concern for authorization under REACH Regulations are present in this boards manufactured by Maderas Mejoradas Industrial s.a., either above the threshold for registration with the European Chemicals Agency or above 0,1% (wt/wt).

## Environmental Information

### Potential environmental impact – mandatory indicators according to EN 15804

Results per declared unit							
Indicator	Unit	A1-A3	C1	C2	C3	C4	D
<b>NATURSOFFIT - W S 8mm</b>							
GWP-fossil	kg CO <sub>2</sub> eq.	2,50E+01	0,00E+00	9,15E-02	9,77E-02	1,44E-02	-6,43E+00
GWP-biogenic	kg CO <sub>2</sub> eq.	-6,81E+00	0,00E+00	4,92E-05	2,93E-03	2,27E+00	7,65E+00
GWP-luluc	kg CO <sub>2</sub> eq.	9,65E-02	0,00E+00	3,26E-05	2,19E-04	3,88E-06	-1,97E-02
GWP-total	kg CO <sub>2</sub> eq.	1,82E+01	0,00E+00	9,16E-02	1,01E-01	2,29E+00	1,20E+00
ODP	kg CFC 11 eq.	2,58E-06	0,00E+00	2,08E-08	8,17E-09	2,05E-09	-8,45E-07
AP	mol H <sup>+</sup> eq.	1,30E-01	0,00E+00	2,63E-04	5,40E-04	4,91E-04	-2,33E-02
EP-freshwater	kg PO <sub>4</sub> <sup>3-</sup> eq.	4,33E-03	0,00E+00	2,24E-06	3,09E-05	8,91E-07	-3,75E-04
EP-freshwater	kg P eq.	1,41E-03	0,00E+00	7,31E-07	1,01E-05	2,90E-07	-1,22E-04
EP-marine	kg N eq.	4,46E-02	0,00E+00	5,20E-05	7,22E-05	2,31E-04	-3,43E-03
EP-terrestrial	mol N eq.	3,21E-01	0,00E+00	5,82E-04	8,85E-04	2,61E-03	-4,06E-02
POCP	kg NMVOC eq.	1,53E-01	0,00E+00	2,23E-04	2,30E-04	6,86E-04	-1,26E-02
ADP-minerals&metals*	kg Sb eq.	3,23E-04	0,00E+00	2,52E-06	3,77E-07	9,02E-08	-2,67E-05
ADP-fossil*	MJ	5,12E+02	0,00E+00	1,38E+00	1,98E+00	1,63E-01	-1,20E+02
WDP	m <sup>3</sup> eq	2,75E+01	0,00E+00	3,91E-03	2,22E-02	5,07E-03	-1,90E+00
<b>NATURSOFFIT - W S 10mm</b>							
GWP-fossil	kg CO <sub>2</sub> eq.	3,15E+01	0,00E+00	1,18E-01	1,24E-01	1,84E-02	-8,16E+00
GWP-biogenic	kg CO <sub>2</sub> eq.	-8,13E+00	0,00E+00	6,32E-05	3,73E-03	2,89E+00	9,71E+00
GWP-luluc	kg CO <sub>2</sub> eq.	1,24E-01	0,00E+00	4,19E-05	2,79E-04	4,94E-06	-2,51E-02
GWP-total	kg CO <sub>2</sub> eq.	2,34E+01	0,00E+00	1,18E-01	1,28E-01	2,91E+00	1,53E+00
ODP	kg CFC 11 eq.	3,22E-06	0,00E+00	2,68E-08	1,04E-08	2,62E-09	-1,07E-06
AP	mol H <sup>+</sup> eq.	1,61E-01	0,00E+00	3,38E-04	6,86E-04	6,24E-04	-2,96E-02
EP-freshwater	kg PO <sub>4</sub> <sup>3-</sup> eq.	5,56E-03	0,00E+00	2,88E-06	3,93E-05	1,13E-06	-4,76E-04
EP-freshwater	kg P eq.	1,81E-03	0,00E+00	9,39E-07	1,28E-05	3,69E-07	-1,55E-04
EP-marine	kg N eq.	5,64E-02	0,00E+00	6,69E-05	9,18E-05	2,94E-04	-4,35E-03
EP-terrestrial	mol N eq.	3,97E-01	0,00E+00	7,48E-04	1,12E-03	3,32E-03	-5,15E-02
POCP	kg NMVOC eq.	1,95E-01	0,00E+00	2,87E-04	2,93E-04	8,73E-04	-1,59E-02
ADP-minerals&metals*	kg Sb eq.	4,05E-04	0,00E+00	3,25E-06	4,79E-07	1,15E-07	-3,39E-05
ADP-fossil*	MJ	6,54E+02	0,00E+00	1,78E+00	2,52E+00	2,08E-01	-1,52E+02
WDP	m <sup>3</sup> eq	3,43E+01	0,00E+00	5,03E-03	2,83E-02	6,45E-03	-2,41E+00
<b>NATURSOFFIT - W F 8mm</b>							
GWP-fossil	kg CO <sub>2</sub> eq.	2,88E+01	0,00E+00	9,31E-02	9,83E-02	1,45E-02	-6,48E+00
GWP-biogenic	kg CO <sub>2</sub> eq.	-6,60E+00	0,00E+00	5,01E-05	2,95E-03	2,29E+00	7,72E+00
GWP-luluc	kg CO <sub>2</sub> eq.	1,23E-01	0,00E+00	3,31E-05	2,21E-04	3,90E-06	-1,99E-02
GWP-total	kg CO <sub>2</sub> eq.	2,24E+01	0,00E+00	9,32E-02	1,01E-01	2,30E+00	1,22E+00
ODP	kg CFC 11 eq.	2,77E-06	0,00E+00	2,12E-08	8,23E-09	2,06E-09	-8,51E-07
AP	mol H <sup>+</sup> eq.	1,51E-01	0,00E+00	2,67E-04	5,43E-04	4,94E-04	-2,35E-02
EP-freshwater	kg PO <sub>4</sub> <sup>3-</sup> eq.	5,49E-03	0,00E+00	2,28E-06	3,11E-05	8,97E-07	-3,79E-04
EP-freshwater	kg P eq.	1,79E-03	0,00E+00	7,44E-07	1,01E-05	2,92E-07	-1,24E-04
EP-marine	kg N eq.	4,85E-02	0,00E+00	5,29E-05	7,26E-05	2,32E-04	-3,47E-03
EP-terrestrial	mol N eq.	3,62E-01	0,00E+00	5,92E-04	8,90E-04	2,63E-03	-4,11E-02
POCP	kg NMVOC eq.	1,69E-01	0,00E+00	2,27E-04	2,32E-04	6,91E-04	-1,27E-02
ADP-minerals&metals*	kg Sb eq.	3,52E-04	0,00E+00	2,57E-06	3,79E-07	9,07E-08	-2,72E-05
ADP-fossil*	MJ	5,74E+02	0,00E+00	1,41E+00	1,99E+00	1,64E-01	-1,21E+02
WDP	m <sup>3</sup> eq	2,80E+01	0,00E+00	3,98E-03	2,24E-02	5,10E-03	-1,92E+00

NATURSOFFIT - W F 10mm							
GWP-fossil	kg CO <sub>2</sub> eq.	3,48E+01	0,00E+00	1,18E-01	1,25E-01	1,86E-02	-8,24E+00
GWP-biogenic	kg CO <sub>2</sub> eq.	-7,88E+00	0,00E+00	6,32E-05	3,76E-03	2,92E+00	9,82E+00
GWP-luluc	kg CO <sub>2</sub> eq.	1,55E-01	0,00E+00	4,19E-05	2,81E-04	4,98E-06	-2,53E-02
GWP-total	kg CO <sub>2</sub> eq.	2,70E+01	0,00E+00	1,18E-01	1,29E-01	2,94E+00	1,55E+00
ODP	kg CFC 11 eq.	3,35E-06	0,00E+00	2,68E-08	1,05E-08	2,64E-09	-1,08E-06
AP	mol H <sup>+</sup> eq.	1,76E-01	0,00E+00	3,38E-04	6,92E-04	6,31E-04	-2,99E-02
EP-freshwater	kg PO <sub>4</sub> <sup>3-</sup> eq.	6,81E-03	0,00E+00	2,88E-06	3,96E-05	1,15E-06	-4,82E-04
EP-freshwater	kg P eq.	2,22E-03	0,00E+00	9,39E-07	1,29E-05	3,73E-07	-1,57E-04
EP-marine	kg N eq.	6,00E-02	0,00E+00	6,69E-05	9,26E-05	2,97E-04	-4,41E-03
EP-terrestrial	mol N eq.	4,30E-01	0,00E+00	7,48E-04	1,13E-03	3,36E-03	-5,22E-02
POCP	kg NMVOC eq.	2,09E-01	0,00E+00	2,87E-04	2,95E-04	8,81E-04	-1,61E-02
ADP-minerals&metals*	kg Sb eq.	4,21E-04	0,00E+00	3,25E-06	4,83E-07	1,16E-07	-3,44E-05
ADP-fossil*	MJ	7,08E+02	0,00E+00	1,78E+00	2,54E+00	2,10E-01	-1,53E+02
WDP	m <sup>3</sup> eq	3,38E+01	0,00E+00	5,03E-03	2,85E-02	6,51E-03	-2,44E+00

GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

\* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

## Potential environmental impact – additional mandatory and voluntary indicators

Indicator	Results per declared unit					
	A1-A3	C1	C2	C3	C4	D
NATURSOFFIT - W S 8 mm						
GWP-GHG <sup>i</sup> Error! Marcador no definido.	2,44E+01	0,00E+00	9,07E-02	9,70E-02	2,07E-02	-6,37E+00
NATURSOFFIT - W S 10 mm						
GWP-GHG <sup>i</sup> Error! Marcador no definido.	3,08E+01	0,00E+00	1,17E-01	1,23E-01	2,65E-02	-8,08E+00
NATURSOFFIT - W F 8 mm						
GWP-GHG <sup>i</sup> Error! Marcador no definido.	2,81E+01	0,00E+00	9,24E-02	9,77E-02	2,08E-02	-6,42E+00
NATURSOFFIT - W F 10 mm						
GWP-GHG <sup>i</sup> Error! Marcador no definido.	3,39E+01	0,00E+00	1,17E-01	1,24E-01	2,67E-02	-8,17E+00

## Use of resources

Indicator	Unit	Results per declared unit					
		A1-A3	C1	C2	C3	C4	D
NATURSOFFIT - W S 8 mm							
PERE	MJ	5,02E+01	0,00E+00	1,98E-02	3,32E-01	7,15E-03	-2,68E+01
PERM	MJ	2,27E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	2,77E+02	0,00E+00	1,98E-02	3,32E-01	7,15E-03	-2,68E+01
PENRE	MJ	5,04E+02	0,00E+00	1,38E+00	1,98E+00	1,63E-01	-1,20E+02
PENRM	MJ.	7,83E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	5,12E+02	0,00E+00	1,38E+00	1,98E+00	1,63E-01	-1,20E+02
SM	kg	1,70E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

FW	m <sup>3</sup>	6,99E-01	0,00E+00	1,48E-04	1,65E-03	7,81E-04	-3,29E-02
<b>NATURSOFFIT - W S 10 mm</b>							
PERE	MJ	5,64E+01	0,00E+00	2,55E-02	4,22E-01	9,12E-03	-3,39E+01
PERM	MJ	2,93E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	3,49E+02	0,00E+00	2,55E-02	4,22E-01	9,12E-03	-3,39E+01
PENRE	MJ	6,46E+02	0,00E+00	1,78E+00	2,52E+00	2,08E-01	-1,52E+02
PENRM	MJ.	7,95E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	6,54E+02	0,00E+00	1,78E+00	2,52E+00	2,08E-01	-1,52E+02
SM	kg	2,19E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m <sup>3</sup>	8,74E-01	0,00E+00	1,90E-04	2,10E-03	9,93E-04	-4,17E-02
<b>NATURSOFFIT - W F 8 mm</b>							
PERE	MJ	3,94E+01	0,00E+00	2,02E-02	3,34E-01	7,19E-03	-2,74E+01
PERM	MJ	2,32E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	2,71E+02	0,00E+00	2,02E-02	3,34E-01	7,19E-03	-2,74E+01
PENRE	MJ	5,66E+02	0,00E+00	1,41E+00	1,99E+00	1,64E-01	-1,21E+02
PENRM	MJ.	7,83E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	5,74E+02	0,00E+00	1,41E+00	1,99E+00	1,64E-01	-1,21E+02
SM	kg	1,61E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m <sup>3</sup>	7,22E-01	0,00E+00	1,51E-04	1,66E-03	7,86E-04	-3,35E-02
<b>NATURSOFFIT - W F 10 mm</b>							
PERE	MJ	4,32E+01	0,00E+00	2,55E-02	4,26E-01	9,20E-03	-3,47E+01
PERM	MJ	2,99E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	3,42E+02	0,00E+00	2,55E-02	4,26E-01	9,20E-03	-3,47E+01
PENRE	MJ	7,00E+02	0,00E+00	1,78E+00	2,54E+00	2,10E-01	-1,53E+02
PENRM	MJ.	7,95E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	7,08E+02	0,00E+00	1,78E+00	2,54E+00	2,10E-01	-1,53E+02
SM	kg	2,10E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m <sup>3</sup>	8,75E-01	0,00E+00	1,90E-04	2,12E-03	1,00E-03	-4,24E-02

## Acronyms

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials;  
 PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources;  
 PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;  
 PENRM = Use of non-renewable primary energy resources used as raw materials;  
 PENRT = Total use of non-renewable primary energy re-sources;  
 SM = Use of secondary material;  
 RSF = Use of renewable secondary fuels;  
 NRSF = Use of non-renewable secondary fuels;  
 FW = Use of net fresh water

## Waste production and output flows

### Waste production

		Results per declared unit					
Indicator	Unit	A1-A3	C1	C2	C3	C4	D
<b>NATURSOFFIT - W S 8mm</b>							
Hazardous waste disposed	kg	6,92E-02	0,00E+00	3,62E-06	8,83E-07	4,25E-07	-1,21E-04
Non-hazardous waste disposed	kg	2,53E+00	0,00E+00	6,73E-02	1,10E-02	1,17E-01	-2,25E-01
Radioactive waste disposed	kg	1,12E-03	0,00E+00	9,42E-06	1,39E-05	5,74E-07	-4,32E-04
<b>NATURSOFFIT - W S 10mm</b>							
Hazardous waste disposed	kg	8,79E-02	0,00E+00	4,66E-06	1,12E-06	5,41E-07	-1,53E-04
Non-hazardous waste disposed	kg	3,13E+00	0,00E+00	8,66E-02	1,40E-02	1,51E-01	-2,85E-01
Radioactive waste disposed	kg	1,42E-03	0,00E+00	1,21E-05	1,77E-05	7,34E-07	-5,48E-04
<b>NATURSOFFIT - W F 8mm</b>							
Hazardous waste disposed	kg	6,96E-02	0,00E+00	3,69E-06	8,88E-07	4,27E-07	-1,22E-04
Non-hazardous waste disposed	kg	2,77E+00	0,00E+00	6,85E-02	1,11E-02	1,17E-01	-2,28E-01
Radioactive waste disposed	kg	1,29E-03	0,00E+00	9,59E-06	1,40E-05	5,77E-07	-4,35E-04
<b>NATURSOFFIT - W F 10mm</b>							
Hazardous waste disposed	kg	8,87E-02	0,00E+00	4,66E-06	1,13E-06	5,46E-07	-1,55E-04
Non-hazardous waste disposed	kg	3,24E+00	0,00E+00	8,66E-02	1,41E-02	1,52E-01	-2,89E-01
Radioactive waste disposed	kg	1,58E-03	0,00E+00	1,21E-05	1,79E-05	7,39E-07	-5,54E-04

### Output flows

		Results declared unit					
Indicator	Unit	A1-A3	C1	C2	C3	C4	D
<b>NATURSOFFIT - W S 8mm</b>							
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Material for recycling	kg	2,01E+00	0,00E+00	0,00E+00	4,91E+00	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	4,71E+00	0,00E+00	0,00E+00
Exported energy, electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,21E+01
Exported energy, thermal	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,68E+01
<b>NATURSOFFIT - W S 10mm</b>							
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Material for recycling	kg	2,55E+00	0,00E+00	0,00E+00	6,24E+00	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	5,99E+00	0,00E+00	0,00E+00
Exported energy, electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,81E+01
Exported energy, thermal	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,22E+01
<b>NATURSOFFIT - W F 8mm</b>							
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Material for recycling	kg	2,02E+00	0,00E+00	0,00E+00	4,94E+00	0,00E+00	0,00E+00

Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	4,74E+00	0,00E+00	0,00E+00
Exported energy, electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,22E+01
Exported energy, thermal	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,72E+01
<b>NATURSOFFIT - W F 10mm</b>							
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Material for recycling	kg	2,57E+00	0,00E+00	0,00E+00	6,29E+00	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	6,04E+00	0,00E+00	0,00E+00
Exported energy, electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,83E+01
Exported energy, thermal	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,28E+01

## Information on biogenic carbon content

Results per declared unit					
BIOGENIC CARBON CONTENT	Unit	QUANTITY			
		NATURSOFFIT – W S 8mm	NATURSOFFIT – W S 10mm	NATURSOFFIT – W F 8mm	NATURSOFFIT – W F 10mm
Biogenic carbon content in product	kg C	3,53E+00	4,45E+00	3,35E+00	4,28E+00
Biogenic carbon content in packaging	kg C	2,11E-01	2,66E-01	2,11E-01	2,67E-01

*Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO<sub>2</sub>.*

## Additional information

The technical datasheet and the safety datasheet can be found in the following webpage:

<https://www.prodema.com/es/catalogos>



---

## Information related to Sector EPD

This is an individual EPD<sup>®</sup>

## Differences versus previous versions

This is the first version of the EPD<sup>®</sup>.

---

## References

- General Programme Instruction of the International EPD<sup>®</sup>System. Version 3.01.
- ISO 14020:2000 Environmental labels and declarations-General principles.
- ISO 14025:2010 Environmental labels and declarations-Type III Environmental Declarations-Principles and procedures.
- ISO 14040:2006 Environmental Management-Life Cycle Assessment-Principles and framework.
- ISO 14044:2006 Environmental Management-Life Cycle Assessment-Requirements and guidelines.
- PCR 2019:14 Construction products. version 1.11
- EN 15804:2012+A2:2019 Sustainability of construction works-Environmental Product Declarations-Core rules for the product category of construction products.

## VERIFICATION STATEMENT CERTIFICATE CERTIFICADO DE DECLARACIÓN DE VERIFICACIÓN

Certificate No. / Certificado nº: EPD00904

TECNALIA R&I CERTIFICACION S.L., confirms that independent third-party verification has been conducted of the Environmental Product Declaration (EPD) on behalf of:

TECNALIA R&I CERTIFICACION S.L., confirma que se ha realizado verificación de tercera parte independiente de la Declaración Ambiental de Producto (DAP) en nombre de:

**PARKLEX PRODEMA INT. S.L.U.**  
**Bº San Miguel 9**  
**20250 LEGORRETA (Gipuzkoa)**

for the following product(s):  
para el siguiente(s) producto(s):

**HPL board with natural wood finish NATURSOFFIT – W**  
**Tablero de HPL con acabado de madera natural NATURSOFFIT – W**

with registration number **S-P-05245** in the International EPD® System ([www.environdec.com](http://www.environdec.com)).  
con número de registro **S-P-05245** en el Sistema Internacional EPD® ([www.environdec.com](http://www.environdec.com)).

it's in conformity with:  
es conforme con:

- **ISO 14025:2010 Environmental labels and declarations. Type III environmental declarations.**
- **General Programme Instructions for the International EPD® System v.3.01.**
- **PCR 2019:14 Construction products (EN 15804:A2) version 1.11.**
- **UN CPC 314 Boards and panels.**

Issued date / Fecha de emisión: 18/01/2022  
Update date / Fecha de actualización: 18/01/2022  
Valid until / Válido hasta: 16/01/2027  
Serial Nº / Nº Serie: EPD0090400-E

*This certificate is not valid without its related EPD.  
Este certificado no es válido sin su correspondiente EPD.*

*El presente certificado está sujeto a modificaciones, suspensiones temporales y retiradas por TECNALIA R&I CERTIFICACION.  
This certificate is subject to modifications, temporary suspensions and withdrawals by TECNALIA R&I CERTIFICACION.*

*El estado de vigencia del certificado puede confirmarse mediante consulta en [www.tecnaliacertificacion.com](http://www.tecnaliacertificacion.com).  
The validity of this certificate can be checked through consultation in [www.tecnaliacertificacion.com](http://www.tecnaliacertificacion.com).*



Carlos Nazabal Alsua  
Manager



**ENAC**  
CERTIFICACION  
Nº 125/C-PR283