



1	GRCLAD	
2	Screws	
	2.1	Panel fastener metal
	2.2	Wall fixing screw - by others
3	Profiles	
	3.1	Aluminum J profile
	3.2	Aluminum HAT profile
	3.3	Jamb profile - by others
	3.4	Sill profile - by others
	3.5	Coronation profile - by others
4	Water resistant barrier - by others	
5	Steel backing plate - by others	
6	Vent. screen - by others	
A	Required min. air chamber $\geq 3/4"$ (20mm)	
B	Circulation of air $\geq 3/4"$ (20mm)	
D	Expansion joint $1/4" - 3/8"$ (6-10mm)	
E	Panel thickness $\geq 1/4"$ (6.4mm)	
F	Distance from the screws to the panel edges $3/4" - 1\ 1/2"$ (20-40mm)	

Measurements in inches are approximate. Real measurements in mm.

Scale 1:2

Measures: inch

<b>PARKLEX PRODEMA</b> www.parklexprodema.com	PRODUCT GRCLAD	SYSTEM EXPOSED SCREW FIXING ON ALUMINUM, WITH BACKING PLATE	DRAWN BY Mikel Maritxalar	DATE 01/2024
	PLAN# GRC1-01-A- C	TITLE DETAIL C-C' // HORIZONTAL JOINT	APPROVED BY Maialen Irastorza	PAGE 4 / 18