



1	NATURCLAD
2	Screws
2.1	Panel fastener metal
2.2	Channel fastener - by others
2.3	Wall fixing screw- by others
3	Profiles
3.1	Aluminum J profile
3.2	Aluminum HAT profile
3.3	Clamp
3.4	Jamb profile - by others
3.5	Sill profile - by others
3.6	Coronation profile - by others
4	Water resistant barrier - by others
5	Thermal insulation - by others
6	Steel backing plate - by others
7	Vent. screen - by others

A	Required min. air chamber $\geq 3/4"$ (20mm)
B	Circulation of air $\geq 3/4"$ (20mm)
C	Horizontal expansion joint $1/16"$ (1mm)
D	Expansion joint $1/4" - 3/8"$ (6-10mm)
E	Panel thickness $5/16"$ (8mm)
F	Distance from the screws to panel edges $3/4" - 1 1/2"$ (20-40mm)

Measurements in inches are approximated. Real measurements in mm.

Scale 1:2

Measures: inch

<b>PARKLEX PRODEMA</b> www.parklexprodema.com	PRODUCT	SYSTEM	DRAWN BY	DATE
	NATURCLAD	LAP SIDING SYSTEM (METALLIC FRAME) WITH BACKING PLATE	Joseba Salbide	01/2022
	PLAN#	TITLE	APPROVED BY	PAGE
	NC1-04-A-F	DETAIL F-F' // WINDOW JAMB	Maialen Irastorza	7 / 12