



1	GRCLAD
2	Screws
2.1	Panel fastener metal
2.2	Wall fixing screw - by others
3	Profiles
3.1	Aluminum J profile
3.2	Aluminum HAT profile
3.3	Jamb profile - by others
3.4	Sill profile - by others
3.5	Coronation profile - by others
4	Water resistant barrier - by others
5	Steel backing plate - by others
6	Vent. screen - by others

A	Required min. air chamber $\geq 3/4"$ (20mm)
B	Circulation of air $\geq 3/4"$ (20mm)
D	Expansion joint $1/4" - 3/8"$ (6-10mm)
E	Panel thickness $\geq 1/4"$ (6.4mm)
F	Distance from the screws to the panel edges $3/4" - 1 1/2"$ (20-40mm)

Measurements in inches are approximate. Real measurements in mm.

Scale 1:2

Measures: inch

<div><div>PARKLEX PRODEMA</div><div>www.parklexprodema.com</div></div>	PRODUCT	SYSTEM	DRAWN BY	DATE
	GRCLAD	EXPOSED SCREW FIXING ON ALUMINUM, WITH BACKING PLATE	Mikel Maritxalar	01/2024
	PLAN#	TITLE	APPROVED BY	PAGE
	GRC1-01-A-J	DETAIL J-J' // DOOR HEAD	Maialen Irastorza	13 / 18