



1	GRCLAD
2	Screws
2.1	Panel fastener metal
2.2	Wall fixing screw - by others
3	Profiles
3.1	Aluminum J profile
3.2	Aluminum HAT profile
3.3	Jamb profile - by others
3.4	Sill profile - by others
3.5	Coronation profile - by others
4	Water resistant barrier - by others
5	Steel backing plate - by others
6	Vent. screen - by others

A	Required min. air chamber ≥ 3/4" (20mm)
B	Circulation of air ≥ 3/4" (20mm)
D	Expansion joint 1/4" - 3/8" (6-10mm)
E	Panel thickness ≥ 1/4" (6.4mm)
F	Distance from the screws to the panel edges 3/4" - 1 1/2" (20-40mm)



Measurements in inches are approximate. Real measurements in mm.

Scale 1:2

Measures: inch

PARKLEX PRODEMA www.parklexprodema.com	PRODUCT	SYSTEM	DRAWN BY	DATE
	GRCLAD	EXPOSED SCREW FIXING ON ALUMINUM, WITH BACKING PLATE	Mikel Maritxalar	01/2024
	PLAN#	TITLE	APPROVED BY	PAGE
	GRC1-01-A-F	DETAIL F-F' // WINDOW JAMB	Maialen Irastorza	7 / 18