



1	GRCLAD
2	Screws
2.1	Panel fastener metal
2.2	Channel fastener - by others
2.3	Wall fixing screw - by others
3	Profiles
3.1	Aluminum J profile
3.2	Aluminum HAT profile
3.3	Z-girt - by others
3.4	Jamb profile - by others
3.5	Sill profile - by others
3.6	Coronation profile - by others
4	Water resistant barrier - by others
5	Thermal insulation - by others
6	Vent. screen - by others
A	Required min. air chamber $\geq 3/4"$ (20mm)
B	Circulation of air $\geq 3/4"$ (20mm)
D	Expansion joint $1/4"$ - $3/8"$ (6-10mm)
E	Panel thickness $\geq 1/4"$ (6.4mm)
F	Distance from the screws to the panel edges $3/4"$ - $1 1/2"$ (20-40mm)

Measurements in inches are approximated. Real measurements in mm.

Scale 1:2

Measures: inch

<div>PARKLEX PRODEMA www.parklexprodema.com</div>	PRODUCT GRCLAD	SYSTEM EXPOSED SCREW FIXING ON ALUMINUM, WITH INSULATION	DRAWN BY Mikel Maritxalar	DATE 02/2024
	PLAN# GRC1-01-B-L	TITLE DETAIL L-L' // VENTILATION DROPPED CEILING	APPROVED BY Maialen Irastorza	PAGE 17 / 18