



| | |
|-----|---|
| 1 | GRCLAD |
| 2 | Screws |
| 2.1 | Panel fastener metal |
| 2.2 | Wall fixing screw - by others |
| 3 | Profiles |
| 3.1 | Aluminum J profile |
| 3.2 | Aluminum HAT profile |
| 3.3 | Jamb profile - by others |
| 3.4 | Sill profile - by others |
| 3.5 | Coronation profile - by others |
| 4 | Water resistant barrier - by others |
| 5 | Steel backing plate - by others |
| 6 | Vent. screen - by others |
| A | Required min. air chamber $\geq 3/4"$ (20mm) |
| B | Circulation of air $\geq 3/4"$ (20mm) |
| D | Expansion joint $1/4" - 3/8"$ (6-10mm) |
| E | Panel thickness $\geq 1/4"$ (6.4mm) |
| F | Distance from the screws to the panel edges $3/4" - 1 1/2"$ (20-40mm) |

Measurements in inches are approximated. Real measurements in mm.

Scale 1:2

Measures: inch

PARKLEX PRODEMA
www.parklexprodema.com

| | | | | | | | |
|---------|--------------|--------|--|-------------|-------------------|------|---------|
| PRODUCT | GRCLAD | SYSTEM | EXPOSED SCREW FIXING ON ALUMINUM, OVER CMU/CEMENT BLOCK | DRAWN BY | Mikel Maritxalar | DATE | 01/2024 |
| PLAN# | GRC1-01-D- A | TITLE | DETAIL A-A' // FAÇADE BASE | APPROVED BY | Maialen Irastorza | PAGE | 2 / 18 |